


texprocess 4 - 7.5.2015

We were there!
Hall 4.0, Stand B51

On display was the **Fully Automatic Roll Slitting machine FA500** and **Euro Collarette 300S** with High Prefeed Device and **True-Drive II**.



FA 500

Heavy Duty Fully automatic



Features

- 2000mm width capacity.*
- 400mm maximum roll diameter.**
- 500mm blade diameter.***
- Touch screen panel.
- Totally enclosed during cut cycle for complete operator safety.
- Adjustable variable speed blade penetration.
- Adjustable variable speed blade and material roll rotation.
- Automatic sharpening of cutting blade with adjustable sharpening time.
- All functions are PLC controlled.
- Automatic blade cooling device with variable settings. (optional)
- Auto - chuck, pneumatic. (optional)
- Mirror - faced version. (optional)

* Other dimensions on request ** FA 600: max.roll ø 500mm *** FA 600: Cutting blade ø 600mm

True Drive II

NEW PLC - control &
Speed - synchronization
of fabric turn-table



Features

- 6" Touch Screen
- Integrated system - less hardware/control buttons
- Full visual view and control of settings
- CANopen PLC/Inverter System
- Display with USB connection
- Very user friendly software
- All settings can be stored under index
- Date can be set for individual fabrics and giving full production output in meter/yard (including Stretch compensation) as well as kg/pound
- Calculation of production efficiency
- Production date stands in archives for analyzing
- Operator log-in
- Easy trouble-shooting and simulation of inputs/outputs on display
- Service intervals can be set including reminder

Specifications and appearance are subject to change without prior notice for improvements.