



TSU 200AF

Tube Sewing Unit 200A/AF

The Svegea Sewing unit 200A/AF sews open fabric into a continuous tubular piece. This is the first stage required to produce Bias Binding. The unit is easy to use, requiring minimal operator assistance.

The Sewing Process

- Open with fabric (up to 200cm/78") passes through a folder.
- Folded edges are automatically aligned, prior to seaming.
- Excess fabric is trimmed away during sewing.
- An in line heated iron, irons the sewn seam.
- The fabric is re-rolled (200A).
- The fabric is flat folded (200AF).

Machine specifications

- Preset stitch counter (for lock stitch, to eliminate the risk of bobbin thread running out).
- Thread break detector.
- Vacuum unit to remove excess trimmed material.
- Electronic machine speed regulator.
- Automatic photo cell edge alignment.
- Variable stitch length.

Technical Data Tube Sewing Unit 200 A/AF

Sewing head	Lockstitch*
Maximum open width	2000 mm (78")**
Maximum roll diameter	400 mm (16")
Power	230 V, single phase, 50/60 cycles
Air supply	6 bar
Machine dimensions	
Floor space	380 x 165 cm (12,5 x 5,5 ft)
Net weight	400 kg (880 lbs)

* Others on request

** Other dimensions on request