

The **Collarette** Cutting Machines



EC 100



EC 200



EC 200-C



EC 200-CS



EC 300



EC 300-S

Technical overview EC-range

Machine type	50	100	200	200-C	200-CS	300	300-S	300-XS
	(semi- automatic)							
Tubular fabric width min* /max <i>*Small tubular diameter fabrics reduce the ability to cut the very wide bands.</i>	27 cm, 11" ∞ cm, ∞"	35 cm, 14" 110 cm, 43"						
Band width, min/max* <i>*Small tubular diameter fabrics reduce the ability to cut the very wide bands.</i>	16 mm, 5/8"							
	200 mm, 8"	170 mm, 6 3/4"			260 mm, 10"	170 mm, 6 3/4"	200 mm, 8"	230 mm, 9"
Max no. of bands.	3	1	2	3	4		5	
Cutting capacity	0-30 m/min 0-33 yds/min	0-40 m/min 0-45 yds/min	2x40 m/min 2x0-45 yds/min	3x40 m/min 3x0-45 yds/min	4x0-60 m/min 4x0-65 yds/min		5x0-60 m/min 5x0-65 yds/min	
Cutting system	Crush cutting	Scissor cutting		Crush cutting		Scissor cutting & crush cutting		
Folded fabric		●	●	●	●	●	●	●
Rolled fabric <i>Preferred device for rolls only, max 82 cm (32")</i>		▲	▲	▲	▲	▲	▲	▲
Folded/rolled fabric <i>high prefeed device, for flat folded and rolled fabric, max 82cm (32").</i> Q-version <i>high prefeed device for flat folded and rolled fabric, max 92cm (36").</i> EC400-version <i>Extra wide frame/turn-table and slide/load platform, max folded length 165 cm (65")</i>		■	■	■	▲	■	▲	▲
		■	■	■	▲	■	▲	▲
		■	■	■	▲	■	▲	▲
Simple E-Drive <i>electronic speed synchronization of fabric turn-table (standard).</i>		●	●	●	●	●	●	●
E-Drive II <i>Electronic speed synchronization for fabric turntable (integrated meter / yard counter optional).</i>		▲	▲	▲	▲	▲	▲	▲
True Drive II <i>PLC-controlled speed synchronization of fabric turn-table (integrated meter/ yard counter included).</i>		▲	▲	▲	▲	▲	▲	▲
Fabric Hole Detector <i>These machines includes an efficient mechanical stop device.</i>		▲	▲	●	●	●	●	●
Festooner <i>For festooning maximum four bands.</i>		▲	▲	▲	▲	▲	▲	▲
Anti-static device		▲	▲	▲	▲	▲	▲	▲
Meter/Yard Counter		▲	▲	▲	▲	▲	▲	▲
Dust-Phantom		▲	▲	▲	▲	▲	▲	▲
Roll-Lifter <i>For easier ergonomic removal of rolls.</i>		▲	▲	▲	▲	▲	▲	▲
Power supply	230V 50-60Hz single phase							
Machine weight	70 kg	135 kg		145 kg	186 kg	145 kg	168 kg	191 kg
Floor space	70x140 cm, (28x55")		100x100 cm, (39x39")					

● = Standard

▲ = Extra

■ = On request



EC 300-XS



EC 50



Accessories



**Prefeed device
for rolls only**



Simple E-Drive



E-Drive II



True-Drive II



**High prefeed
device**



Roll-lifter



Festooner



Dust-Phantom



EC400-S / XS

Specifications and appearance are subject to change without prior notice for improvements.